


TCS310 – Thermocouple Sensor with Connection Head & Thread

TCS310

Sensor Configuration	
Simplex	S
Duplex	D
Triplex	T
Sensor Type	
Type E	E
Type J	J
Type K	K
Type N	N
Type T	T
Sensor Junction	
Isolated	I
Grounded	G
Exposed	E
Sheath Material	
310 Stainless Steel	310
316 Stainless Steel	316
Alloy 600	600
Sheath Diameter Ø	
6mm	6
Xmm	X
Sheath Length (L)	
Xmm	X
Thread Size	
¼"	14
½"	12
¾"	34
1"	1
M20 x 1.5	M20
Thread Type	
BSPP	BP
BSPT	BT
NPT	NT
Metric	M
Approvals	
ATEX/IECEX Exia II 1 GD	IA
ATEX/IECEX Exd II 2 GD	XD
None	X
Connection Head	
Type 11 (Aluminium)	11
Type 16 (Aluminium)	16
Type 44 (316 Stainless Steel)	44
Type 46W (Plastic)	46W
Type 55/A (Aluminium)	55A
Type 55/S (316 Stainless Steel)	55S
Termination	
150mm Tails	TA
Ceramic Terminal Block	TB
HBS4200 Temperature Transmitter	42
HBS4400 Temperature Transmitter (Exia)	44
HBS4600 Temperature Transmitter (Exia, HART)	46
HBS5500 Temperature Transmitter & Indicator (HART)	55
HBS5600 Temperature Transmitter & Indicator (Exia, HART)	56
Indicator	
HBS3300	33
HBS3700 (Battery Powered)	37
HBS5500 Temperature Transmitter & Indicator (HART)	55
HBS5600 Temperature Transmitter & Indicator (Exia, HART)	56
None	X



Example Ordering Code:

TCS310-S-K-I-316-6-150-12-BP-X-11-42-X